

MATERIAL SAFETY DATA SHEET

Section 1 – CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: PREMICOTE 683 UV B
Identification Number: HTS 683 UV B, PREMICOTE 683 UV B
Product User/Class: Resin blend with flammable liquids

For Technical or Emergency Information: (Monday – Friday, 8:00 A.M. to 5:00P.M. CT.)

Supplier:

Premium Spray Products Canada
 190 Hodsman Road
 Regina, Sask., S4N 5X4
 (306)721-1339

Preparer: Regulatory Department

Revision Date: 02/02/2012

In the event of a chemical emergency involving a spill, leak, fire, exposure or accident during transportation,
 call CHEMTREC: 800-424-9300 (24 hours). Read the MSDS and label prior to use.

SECTION 2 – HAZARDOUS COMPONENTS

--- Exposure Limits ---

	<u>CAS #</u>	<u>Weight %</u>	<u>SARA 313</u>	<u>ACGIH TWA</u>	<u>ACGIH STEL</u>	<u>OSHA PEL</u>	<u>CERCLA RQ (lbs)</u>
Xylene	1330-20-7	15-30	YES	100 ppm	150 ppm	100 ppm	100
Ehtylbenzene	100-41-4	7-13	YES	100 ppm	125 ppm	100 ppm	1000
Decabromodiphenyl oxide	1163195	1-5	YES	10mg/m3	N.E.	15mg/m3	NA
Tris(B-chloropropyle) phosphate	13674-84-5	3-7	NO	NDA	NDA	NDA	NA
Toluene	108-88-3	5-10	YES	100ppm	NDA	100ppm (C)	1000
Antimony Oxide	1309-64-4	1-5	YES	0.5mg/m3	NDA	0.5mg/m3	NA

Note: The dried film of this product may become a dust nuisance when removed by sanding or grinding. OSHA recommends a PEL/TWA of 15mg/m3 for total dust and 5mg/m3 for the respirable fraction. ACGIH recommends a TLV/TWA of 10mg/m3 for total dust.

SECTION 3 – PHYSICAL DATA

ODOR:	Aromatic	EVAPORATION RATE:	<1 (Ether = 1)
BOILING POINT:	>170°F	VAPOR DENSITY:	>1 (Air = 1)
% VOLATILE BY WEIGHT:	16-25	SOLUBILITY IN WATER:	Not soluble
% VOLATILE BY VOLUME:	35-44	WEIGHT PER GALLON:	13.8-14.2

NE=Not Established

NDA=No Data Available

C = Ceiling

SECTION 4 – HEALTH INFORMATION

Emergency Overview: Extremely flammable. Take precautions when handling such as grounding the container. Harmful if inhaled. Toxic fumes are released in fire situations.

HMIS RATINGS:	Health 2	Flammability 3	Reactivity 0
Insignificant = 0	Slight = 1	Moderate = 2	High = 3
NFPA RATINGS:	Health 2	Flammability 3	Reactivity 0
Minimal = 0	Slight = 1	Moderate = 2	Serious = 3
			Severe = 4

Potential Health Effects: The information listed below is based on the individual components of this mixture.

Inhalation: Heating, spraying, foaming, or otherwise mechanically dispersing (drumming, venting or pumping) operations of this blend may generate more vapor or aerosol concentrations of its components. High vapor concentrations may cause dizziness, headaches, nausea, loss of balance and coordination, unconsciousness, coma or respiratory failure. Repeat excessive exposures may cause liver and kidney effects or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage.

Skin Contact: Prolonged contact may lead to reddening, burning, drying, cracking, skin burns, and may result in absorption of amounts sufficient to cause depression of the central nervous system.. Pre-existing skin disorders may be aggravated by exposure to this material. may result in absorption of amounts sufficient to cause depression of the central nervous system.

Eye Contact: Will cause irritation on contact. Symptoms from exposure include stinging, watering or discomfort of the eyes with redness and swelling.

Ingestion: Harmful or fatal if swallowed. Aspiration Hazard – Can enter lungs during swallowing or vomiting and cause lung inflammation and damage. Symptoms include nausea, vomiting, diarrhea, dizziness, weakness, fatigue and headache.

Carcinogenicity: Chemicals contained in this product that are listed by the NTP, IARC or regulated by OSHA as carcinogens: Ethylbenzene-IARC (possible human carcinogen)

SECTION 5 – EMERGENCY AND FIRST AID PROCEDURES

Eyes: Flush eyes with plenty of water for at least 15 minutes. Use fingers to assure that the eyelids are separated and that the eye is being irrigated. Consult a physician.

Skin: Remove all contaminated clothing and shoes. Wash skin with large quantities of water and soap. Wash clothing before wearing again and clean shoes. If redness, itching or a burning sensation develops or persists after the area is washed, consult a physician.

Ingestion: If swallowed, do not induce vomiting unless directed to do so by medical personnel. This material is an aspiration hazard. Never give anything by mouth to an unconscious person. Seek medical attention.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility immediately.

SECTION 6 – FIRE AND EXPLOSION HAZARDS**Flash Point:** >45°F, (COC)**Autoignition Temperature:** NDA**Flammable Limits (STP):** NDA**Flammability Classifications:**

OSHA – Flammable Liquid – Class 1B

DOT – Flammable Liquid

Fire Degradation Products: Combustion may produce carbon dioxide, carbon monoxide, nitrogen oxides and other toxic fumes.**Extinguishing Media:** Use dry chemical, foam, carbon dioxide, halogenated agents or water. Use cold water spray to cool fire-exposed containers to minimize risk of rupture. A solid stream of water directed into the hot burning liquid could cause frothing. If possible, contain fire run-off water.**Protective Equipment:** Positive-pressure self-contained breathing apparatus with full face-piece and full protective clothing should be worn by fire-fighters.**SECTION 7 – REACTIVITY****Stability:** This is a flammable material. Avoid high temperatures, sparks, flame and extended exposure over 85°F (25°C).**Hazardous Polymerization:** Will not occur.**Reactivity:** Incompatible with oxidizing materials, strong alkalies, amines and acids.**SECTION 8 – EMPLOYEE PROTECTION****Ventilation:** Local exhaust ventilation is recommended when working with this product. Uses requiring heating and/or spraying may require more ventilation or personal protective equipment.**Respiratory Protection:** The specific respirator selected must be based on contamination levels of this blend found in the workplace and must not exceed the working limits of the respirator and be jointly approved by NIOSH and MSHA. In areas of high concentrations, fresh air-line respirators or self-contained breathing apparatus should be used. A positive pressure self contained breathing apparatus can be used in emergencies or other unusual situations.**Eye Protection:** Fitted chemical goggles or full face shield and safety glasses must be used consistent with splash hazard present. If vapor exposure causes eye discomfort, use a full face-piece respirator or supplied air hood.**Protective Clothing:** Wear clothing, boots and gloves resistant to permeation of product. Materials may include butyl rubber, nitrile rubber, neoprene and Saranex® coated Tyvek®.**Other Protective Equipment:** An eyewash station and safety shower or other drenching facilities are recommended in the work area.

SECTION 9 – ENVIRONMENTAL PROTECTION

Spill: Isolate and confine spill area. Remove all sources of ignition sources like flames, heating elements, gas engines, etc. Use non-sparking tools. Emergency clean-up personnel should select the specific respirator based on contamination levels found. Use air purifying respirator equipped with full-face organic vapor cartridge if vapors are detected, or are irritating. In areas of high concentrations, fresh air-line respirators or self-contained breathing apparatus and protective clothing should be used. Prevent spreading and contamination of surface waters and drinking supplies. Notify local health officials and other appropriate agencies if such contamination should occur.

Clean up: With adequate ventilation and appropriate personal protective equipment, cover the area with an inert absorbent material such as clay or vermiculite and transfer to steel waste containers. The spill area should then be washed down with soap and water to dilute and remove remaining traces of material. Ventilate area to remove the remaining vapors.

Disposal: Any disposal practice must be in compliance with all federal, state and local laws and regulations. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate or otherwise inappropriate. Waste characterization and disposal compliance are the responsibility solely of the party generating the waste or deciding to discard or dispose of the material.

Do not allow material to enter sewers, a body of water, or contact the ground. Refer to RCRA 40 CFR 261, and/or any other appropriate federal, state or local requirements for proper classification information.

Container Disposal: Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

Call CHEMTREC (800-424-9300) for chemical emergencies or spills during transportation

SECTION 10 - STORAGE AND HANDLING

Storage: When stored between 15 and 30°C (60 and 85°F) in sealed containers, typical shelf life is 6 months or more from the date of manufacture. Consult technical data sheet for shelf life requirements affecting performance quality. Opened containers must be handled properly to prevent moisture pickup.

Handling: Extremely flammable. Ground containers. Avoid skin and eye contact. Use personal protective equipment when transferring material to or from drums, totes or other containers. If contamination with isocyanates is suspected, do not reseal containers. Do not smoke or use naked lights, open flames, space heaters, or other ignition sources near pouring, frothing or spraying operations. Material can ignite if exposed to open flames.

SECTION 11 – SHIPPING INFORMATION

DOT (Domestic Surface)

Shipping Name:

Hazard Class or Division:

ID Number:

Hazard Label:

Packaging Group

ERG#127

Paint

3

UN1263

Flammable Liquid

PG II

SECTION 12 – REGULATORY INFORMATION

OSHA Status: This product is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: On the TSCA inventory.

SARA Title III:

Section 302 Extremely Hazardous Substances:

None

Section 311/312 Hazard Categories:

Fire Hazard, Immediate Health Hazard, Delayed Health Hazard

RCRA Status: It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. (40 CFR 261.20-24)

California Proposition 65: Chemical(s) in this product known to the State of California to cause cancer:

Antimony Oxide, Benzene

California Proposition 65: Chemical(s) in this product known to the State of California to cause reproductive toxicity:

Antimony Oxide, Benzene, Toluene

SECTION 13 – COMMENTS

This MSDS complies with 29 CFR 1910.1200 (Hazard Communication Standard)

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described herein.